

Adaptive and Constraint-Aware Data Placement for S3-Compatible Storage

Marcell Feher
Chocolate Cloud ApS



ML4ECS Workshop, 26/01/2026, Krakow



Distributed, Provider-Independent Object Storage

System Baseline	Benefits	Limitations (pre-MLSysOps)
<ul style="list-style-type: none">• S3-compatible object storage• Per-object pipeline<ul style="list-style-type: none">◦ Sharding◦ Compression◦ AES-256 encryption◦ Erasure coding (k-of-n) with redundancy• Fragments distributed<ul style="list-style-type: none">◦ Multiple cloud providers◦ Multiple regions◦ Optional on-prem backends	<ul style="list-style-type: none">• No single provider holds reconstructable data• Resilience to provider and regional failures• Strong data sovereignty guarantees	<ul style="list-style-type: none">• Storage Policies are static and manually defined<ul style="list-style-type: none">◦ Policy: EC parameters and explicit backend placement• One policy per bucket, applied uniformly to all objects

Technical problem to solve in MLSysOps:
How to adapt data placement when **traffic patterns, constraints or objectives change?**



Online Storage Policy Migration

Initial Contribution

- Introduced bucket-wide policy migration
- Users can update:
 - Erasure coding parameters (redundancy)
 - Backend provider/region assignments
- System migrates existing objects to the new policy
- Online process (no bucket downtime)
- Transparent for users and applications
- Deterministic final state

Why this matters

- Decouples data lifetime from policy lifetime
- Enabled policy evolution without re-upload
- Serves as a **building block for automation**

Policy migration turns static configuration into a controllable operation



Intent-Driven Storage Policies

High-level interface

- Users specify objectives, not placement
- Optimize for:
 - Download latency
 - Egress cost
 - Proximity to users
- Constraints supported:
 - Geo-fence (allowed countries)
 - GDPR mode (no provider stores 100% data)
 - Metro-level outage resilience
 - Max cost (\$/TB)
 - Min speed

Key shift in approach

- Explicit placement → constraint satisfaction
- Policy generation is an optimization problem

Results

- System generates a concrete storage policy, not the user
- Policy is valid if all constraints are satisfied



Traffic-Aware, Closed-Loop Adaptation

Observability inputs

- Per-bucket access telemetry
 - Download volume
 - Request origin distribution
 - Serving gateway location
- Storage backend performance
 - Measured throughput from real downloads
 - Per gateway-backend pair

Characteristics

- Feedback-driven (not rule-based)
- Autonomous but bounded by user constraints
- Migration is the actuation mechanism

MLSysOps spirit

- Applies control loops to storage, not just compute
- Treats data placement as a managed system
- Integrates monitoring → decision → actuation

Control loop

- Periodic evaluation of recent traffic
- Solve for optimal policy under constraints
- Compare with current policy
- If different → trigger migration

DEMO



Current Challenges

Better Policy Generation

- Forecast bucket traffic (instead of looking at the recent past)
- Change redundancy when traffic volume changes and constraints allow
- Consider current policy and cost of the migration itself
- Introduce user-defined cost limits for migrations
- Additional controls (e.g., add green energy to the optimization mix)

Finer granularity

- Object or sub-object level traffic profiling, policy eval and migrations



Thank You!